

Wire-to-Board-Connectors



Click on each product information to jump to the web.

Series	ISH				ISHV	
Feature						
	Miniaturized 125 °C resistance horizontal mating connector	Dedicated Power Pin	Miniaturized 125 °C resistance vertical mating connector	Miniaturized 125 °C resistance wire-to-wire connector	Miniaturized 125 °C resistance LV214 compatible connector	Miniaturized 125 °C resistance LV214 compatible connector
Mating Type	Horizontal		Vertical	Wire to Wire	Horizontal	Vertical
Available Pin Count	3 (1 row) 6/8/12/16/20/32 (2 rows)	20/28 (2 rows) (20 P) Signal 18+Power 2 (28 P) Signal 26+Power 2	10/20/26 (2 rows)	3 (1 row) 8 (2 rows)	12/16 (2 rows)	8 (2 rows)
Pitch	2.0 mm	Signal : 2.0 mm Power : 3.8 mm	2.0 mm			
Pin Size	0.50 mm * 0.40 mm (020)	Signal: 0.50 mm*0.40 mm (020) Power: 1.50 mm*0.64 mm (060)	0.50 mm * 0.40 mm (020)			
Mating Height	7.50 mm (1 row) 12.20 mm (2 rows)	13.60 mm	20.75 mm	8.00 mm (1 row) 11.70 mm (2 rows)	10.88 mm (2 rows)	19.95 mm
Current Rating	4.5A per pin	Signal 4.5A per pin Power 7A per pin	4.5A per pin			
Operating Temperature	-40 – 125 °C					
Vibration Resistance	10 G					
Plating	Sn					
Automotive Standards	USCAR-2 (*)	USCAR-2 (**)	LV214	LV214 (***)	LV214	LV214

Note (*) : 8P and 12P complied, except for Retention Force specification. (**) : 20P complied, except for retention force of male power terminals. (need to add rear cover option) (***) : 8P complied



Wire-to-Board-Connectors

Click on each product information to jump to the web.

Series	IARPB	
Feature		
	Miniaturized board-in connector	Miniaturized board-in vertical type connector
Mating Type	Through-Hole DIP	
Available Pin Count	2/3/4/5/6 (1 row)	2/4/5/6/7 (1 row) *3,8,9,10(planned)
Pitch	2.5 mm	
Pin Size	Φ 0.7	
Mating Height	Max 3,50 mm (2,3,4,5P) Max 4,0mm (6P)	Max 8,70mm
Current Rating	3.0A per pin	
Operating Temperature	-40 ~+125°C	
Vibration Resistance	10G	6G
Plating	Sn	
Automotive Standards	-	

Terminals

Click on each product information to jump to the web.

Series		AP-10	AP-TSS10 / AP-LT10	
Feature				
		High current (16A), High temperature (105°C) resistance, board-to-board power supply terminal	High current (32 A), high temperature (125°C) Spacer/Power Terminal, PCB SMT Terminal, easily operates with SMT and M3 (8.00 mm) screws	
Mating type		Vertical	Vertical (M3 thread screw)	
Size (mm)	Height (mm)	11.70 +/- 0.20 (Receptacle)	8.00 +/- 0.10 (AP-TSS10) 1.00 +/- 0.10 (AP-LT10)	
		7.50 +/- 0.10 (Plug: 7.5)		
		14.50 +/- 0.10 (Plug: 14.5)		
	Width (mm)	7.60 +/- 0.20 (Receptacle)		Φ 7.00 +/- 0.10 (AP-TSS10) Φ 8.20 +/- 0.10 (APLT-10)
		6.00 +/- 0.10 (Plug: 7.5)		
		7.60 +/- 0.10 (Plug: 14.5)		
	Depth (mm)	3.40 +/- 0.20 (Receptacle)		
		3.40 +/- 0.20 (Plug: 7.5)		
		5.20 +/- 0.20 (Plug: 14.5)		
Plating Type		Sn / Ni plating	Sn / Ni plating	
Rating Amperage		16A DC	32A DC	
Operating Temperature		233~378 (-40~+105°C)	233~398 (-40~+125°C)	
Contact resistance		1.0 mΩ Max.	1.0 mΩ Max.	
Operating Humidity		85 % Max. (Non-Condensing)	85 % Max. (Non-Condensing)	
Durability		3 CYCLES	-	

I-PEX Product Series



MHF[®]
Series
RF Connectors



EVAFLEX[®]
Series
MINIFLEX[®]
Series
FPC/FFC Connectors



AP
Series
Terminals



CABLINE[®]
Series
Micro-Coaxial/ Twinax
Connectors



ISH[®]
Series
IARPB[®]
Series
Wire-to-Board
Connectors



MINIDOCK[™]
Series
I/O Connectors



NOVASTACK[®]
Series
Board-to-Board
Connectors

 Please [contact us](#) for custom products.



I-PEX, MHF, CABLINE, NOVASTACK, EVAFLEX, MINIFLEX, ISH, IARPB, IASLP, ESTORQ, i-Fit and ISFIT are registered trademarks of I-PEX Inc. Please note that the contents in the catalog might be changed without prior notification. I-PEX Inc. assumes no responsibility for any inaccuracies or obligation to update Information on these documents. Please be sure to read and understand the latest "Precautions for Use" and "Instruction Manual" before you use our products. We shall not be responsible for any defects, damages or troubles in case you use our products without following the precautions for use. Please feel free to contact our sales representatives when you use our products for any applications that require very high reliability and safety, or that relate to human life (ex. nuclear power control, aerospace, transportation, medical equipment, safety equipment etc.).

Contact your sales representative for more detailed information. [i-pex.com]

I-PEX Inc.